FWDS42H2/DS

42" S-series Digital Signage Bundle

$4,400.00

U.S.List Price

UPC: 027242279308

Overview

Simple Signage Solutions from Sony are easy-to-use digital signage packages that allow small businesses to employ effective signage simply and easily. Each bundle includes a high-performance FWD display, plus a Hyper Media Player (HMP) containing user-friendly templates and management software, and the required connecting cable. Screens can have multiple zones, each containing a variety of content, such as a clock, real-time weather, traffic, or other news feed via RSS, pictures and/or video from files or streaming video content, freeform text, or bulleted lists. The built-in drag-and-drop interface makes it simple to create pages and programs quickly and easily. Since it runs in a browser, signs can even be updated from a wireless tablet or smartphone, or from a remote location. Because the displays use LED backlighting and the player uses only 3-6 watts of power, this signage solution is eco-friendly.

Highlights

* Full HD 1920x1080 panel
* 700 cd/m2 brightness
* Landscape or Portrait orientation
* Professional grade for 24/7 operation
* LED backlight
* Full complement of video interfaces
* Both RS-232 and RJ45 control interfaces
* Thin bezel
* Burn-in resistant LCD technology
* VESA-compliant mounting points
* Template-based content creation
* Drag and drop interface
* Browser-based for anytime, anywhere access
* RSS integration
* Full template library
* 1080p Full HD Hyper Media Player
* Internal solid state 8G hard drive with external flash drive and hard drive via USB
* No PC so it’s secure from virus and Windows® issues
* Simple zero config network integration
* Dynamic content: RSS feeds, widgets (weather, clocks, effects), animations, instant messaging, queue management
* Dynamic zones to position multiple Full HD videos and other media wherever you want
* Comprehensive scheduling options
* The FWDS42H2 is TAA compliant

Features

Features	Benefits
Display and Player in One Box	Set up and use quickly and easily
User-friendly Templates Included	Create effective signage quickly and easily
Browser-based Interface	Signs can be updated from wireless tablet or smart phone, or from a remote location
LED backlit displays and 3-6 watt player	Eco-friendly

Professional-grade LCD panel	24x7 operation and portrait or landscape orientation

Specifications

Audio Specifications	Detail
Audio Amp	L/R, 7W + 7W, 6 ohms
Computer Formats Specifications	**Detail**
1024 x 768	Yes
1152 x 864	Yes
1280 x 1024	Yes
1280 x 768	Yes
1280 x 960	Yes
1360 x 768	Yes
1400 x 1050	Yes
1600 x 1200	Yes
1920 x 1080	Yes
640 x 480	Yes
800 x 600	Yes
Contol Inputs Specifications	**Detail**
9 pin Dsub Parellel	(D-sub 9-pin, straight)
Network	(RJ45, 10BASE-T/100BASE-TX)
Digital Inputs Specifications	**Detail**
DVI-D	DVI in with audio in Rev. 1.0 compliant
HDMI	HDMI(1080p) in with audio in
HDSDI (SMPTE 292M)	Option via BKM-FW16
SDI (SMPTE 259M)	Option via BKM-FW16
Digital Signage Specifications	**Detail**
Management Software	Fusion (pre-loaded)
Media Player	HMP-200 (included)
Player Power Consumption	3 W (typical) 6 W (maximum)
Player Resolution	1920 x 1080p full HD
Player Warranty	Lifetime Limited Warranty
Zone or Layers	Unlimited
Display Specifications	**Detail**
Backlight Technology	Edge lit type LED Backlight
Brightness	700 cd/m2 (typical)
Contrast Ratio	4,000 : 1 (typical)
Display Technology	a-Si TFT Active Matrix LCD
Resolution	1920 x 1080 pixels, Full HD
Screen Size	42 inches
Viewing Angle	178 degrees (typical)
General Specifications Specifications	**Detail**

Dimensions (W x H x D)	38 1/8 x 22 1/8 x 3 1/2 inches (excluding protruding parts)
Wall/Arm Mount	VESA 400mm x 400mm
Weight	44.5 lb

Input Formats Specifications	**Detail**
Analog RGB (15 pin DSub)	HD15 in with audio in
Analog RGB (BNC)	(RGB/Component Video)
Analog Y Pb Pr	(Pin jack (x3))
Composite	(BNC (x2))

Operating Conditions Specifications	**Detail**
Operating Humidity	20% to 90%, no condensation
Operating Temperature	32°F to 104°F
Storage Temperature	14°F to 104°F

Power Requirements Specifications	**Detail**
Power Consumption	108 W (typical) 145 W (maximum)
Power Requirements	"AC 100 V to 240 V, 50/60 Hz, 1.45 A (maximum)"

Service and Warranty Information Specifications	**Detail**
Limited Warranty Term	3 yr Limited Warranty

Video Image Formats Specifications	**Detail**
1080 24Psf	Yes
1080 60P	Yes
1080 60i	Yes
480 60i	Yes
576 50i	Yes
720P 50 or 60Hz	Yes

Accessories

Supplied Accessories

Model:	**Description:**	**U.S.List Price**
	AC power cord (x2), AC plug holder (x2), Cable holder (x6), Remote Control RM-FW002 (x1), Size AA (R6) batteries (x2), Operating instructions (x1)	Pricing available upon request

Optional Accessories

Model:	**Description:**	**U.S.List Price**
	"BKM-FW16 , SU-S02 , SS-SPG02"	Pricing available upon request

Resources

Brochure

Description:	**Release Date**	**Type/Size**

Signage Solutions		pdf / 1,041K
Sony public displays: the picture of perfection		pdf / 1,099K

User Manual

Description:	Release Date	Type/Size
Operating Instructions - FWD-S46H2/S42H2		pdf / 13,458K

This PDF was printed at sony.com/professional. Copyright 2011, Sony Electronics Inc All Rights Reserved.